

## NVR808H-64

64 Channel 2U 8HDD Network Video Recorders



### Key Features

- 64CH IP video input, up to 12MP
- H.265+/H.265 dual-stream video compression
- Incoming/Outgoing bandwidth: 1024Mbps/800Mbps (without raid)
- Decoding: 32CH 1080P@30fps/16CH 4Mp@30fps/8CH 8Mp@30fps/5CH 12Mp@30fps
- Supports mainstream cameras of ONVIF and RTSP protocol
- AI by camera: SMD, perimeter protection, face detection, etc.



### Professional and Reliability

- H.265+ compression effectively reduces storage requirements by up to 75%
- Third-party cloud storage integration -Google Drive and Dropbox for video backup

### Stability

- N+1 hot spare
- Automatic network replenishment
- RAID 0, 1, 5, 10

### Third-Party Compatibility

- Supports ONVIF and RTSP protocols for seamless integration with third-party cameras

### Smart Search and Playback

- Smart search and smart playback for the smart events triggered by humans or vehicles

### HD Video Output

- Support 4 x HDMI and 2 x VGA outputs
- Provide heterologous output for the 4 HDMI ports
- HDMI video output at up to 8K resolution

## Storage and Playback

- Up to 8 SATA interfaces (up to 22 TB capacity per HDD)
- 16-ch synchronous playback

## Network & Ethernet Access

- Dual self-adaptive 10/100/1000/2500Mbps Ethernet interface
- Homaxi-view app for easy network management


## Specification

Video & Audio Input		
IP Video Input	64 ch	
Audio Input	1-ch, RCA	
Video & Audio Output		
HDMI	HDMI 1: 7680 × 4320/30Hz, 3840 × 2160/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz HDMI 2: 3840 × 2160/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz HDMI 3: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz HDMI 4: 3840 × 2160/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz	
VGA	VGA 1: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz VGA 2: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz	
Video Output	2-channel VGA, 4-channel HDMI video output	
	Simultaneous	max. resolution of HDMI1 is 8K max. resolution of HDMI2 and HDMI4 is 4K max. resolution of VGA1 VGA2 and HDMI3 is 1080p
	Heterologous	Simultaneous video source output for VGA1 and HDMI4 Simultaneous video source output for VGA2 and HDMI2 max. resolution of HDMI1 HDMI4 and HDMI2 is 4K, max. resolution of HDMI3 is 1080P max. resolution of VGA1 and VGA2 is 1080P
Main Screen (screen split)	1, 4, 8, 9, 16, 25, 36, 64 screen split	
Secondary Screen (screen split)	1, 4, 8, 9, 16, 25, 36 screen split	
Audio Output	2-ch, RCA	
Recording		
Compression	H.265+/H.265/H.264+/H.264	
Resolution	12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF	
Playback & Backup		
Playback Resolution	12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF	


Decoding Capability	H.265	32-ch @ 1080P 30fps 16-ch @ 4Mp 30fps 8-ch @ 8Mp 30fps 4-ch @ 16Mp 30fps 2-ch @ 32Mp 30fps
	H.264	16-ch 1080P @ 30fps 8-ch 4Mp @ 30fps 4-ch 8Mp @ 30fps 2-ch 16Mp @ 30fps 1-ch 32Mp @ 30fps
Synchronous Playback	16 ch @ 1080P 30fps/16 ch @ 4Mp 30fps/8 ch @ 8Mp 30fps/5ch @ 12Mp 30fps	
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback	
Backup Mode	USB Device/Network/eSATA	
<b>Advanced Features</b>		
Smart Detection By Camera	Area Intrusion, Line crossing, Region Entrance /Region Exiting, Fast Moving, Object Missing, Unattended Object, Loitering Detection, Parking Detection, Face Detection, People Gathering Detection, Blurred detection, Scene change detection, Audio exception detection,SMD,PP	
Smart Playback	Face Detection/Line Crossing/Are Intrusion/Motion Detection	
Cloud Storage	Support	
Cloud Upgrade	Support	
<b>Network</b>		
Incoming Bandwidth	1024Mbps (without raid) /512Mbps (raid)	
Outgoing Bandwidth	800Mbps (without raid) /400Mbps (raid)	
Ethernet	2 x RJ-45 10 /100 /1000/2500Mbps self-adaptive Ethernet interface	
Protocols	HTTPS, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF	
Mobile Surveillance	IOS, Android	
<b>Hard Disk</b>		
SATA	8 SATA interface	
Capacity	Up to 22TB capacity for each HDD	
RAID	RAID 0, 1, 5, 10	
<b>External Interface</b>		
USB Interface	Front panel: 2 x USB 2.0 Rear panel: 2 x USB 3.0	
eSata	1 x eSATA	
RS 485	1-ch	
RS 232	1-ch	
12V Out	1-ch	
Alarm In	16-ch	
Alarm Out	8-ch	

General	
Operating Conditions	(-10°C ~ 55°C) (14°F ~ 131°F) Humidity 10% to 90%
Power Supply	AC 100 ~ 240 V
Power Consumption	MAX. 30 W (without HDD)
Dimensions (W x D x H)	17.32" x 17.80" x 3.54", 2U (440 x 452 x 90 mm)
Gross Weight	17.63 lb (8 kg)

## Dimensions



## Rear Panel



No.	Description	No.	Description
1	Power Switch	7	Network Port
2	Power Input	8	Audio IN/OUT RCA
3	Ground	9	VGA Port
4	Alarm Input	10	RS232 Port
5	Alarm Out	11	HDMI Port
6	e SATA Port	12	USB Port